


UNIMAC PLUG VALVES



| NO. | PART | QTY. | MATERIAL |
|-----|------------------|-------|----------------------------------|
| 1 | BODY | 1 | CAST IRON, IS 210, GR FG 220/260 |
| 2 | TOP COVER | 1 | CAST IRON, IS 210, GR FG 220/260 |
| 3 | PLUG | 1 | CAST IRON, IS 210, GR FG 220/260 |
| 4 | GLAND | 1 | CAST IRON, IS 210, GR FG 220/260 |
| 5 | LUBRICANT BOLT | 1 | CARBON STEEL |
| 6 | NON RETURN VALVE | 1 | CARBON STEEL |
| 7 | GASKET | 1 | C A F |
| 8 | SHIM | 1 | S.S. 304 |
| 9 | COVER BOLTS | 2 | CARBON STEEL |
| 10 | STUDS & NUTS | 2 + 4 | CARBON STEEL |
| 11 | GLAND PACKING | 2 | ASBESTOS |

Note : Due to constant up gradation, dimensions are subject to change by the manufacturer.


Plug Valves with Flanged Enda are available from 1/2" to 4" in Regular Pattern & Short Pattern , Screwed from 1/2" to 1"

Wrenches for all sizes available when ordered seperately.

Flanges : As per B.S. 10 Table D, E, F Class 150 or ANSI 16.1 Class 125
Screwed : BSP Thread as per BS 21

Flanged Valves are offered undrilled.

Drilling can be done on request.



Note : Due to constant up gradation, dimensions are

subject to change by the manufacturer.

| DIMENSIONS | | REGULAR PATTERN | | | | | | | | | SHORT PATTERN | | | | | |
|-------------------------------|-----------|-----------------|------|-----|-----|-----|------|-----|-----|-----|---------------|-----|-----|-----|-----|-----|
| SIZE OF VALVES (mm) | | 15 | 20 | 25 | 40 | 50 | 65 | 80 | 100 | 150 | 50 | 65 | 80 | 100 | 150 | |
| SCREWED END TO END | | A | 89 | 95 | 111 | | | | | | | | | | | |
| FACE TO FACE | | A | 120 | 120 | 141 | 166 | 202 | 221 | 242 | 306 | 393 | 179 | 190 | 202 | 230 | 268 |
| FLANGE DIAMETER | BST 'D' | | 83 | 101 | 114 | 133 | 152 | 165 | 184 | 216 | 279 | 152 | 165 | 184 | 216 | 279 |
| | BST 'F' | B | 95 | 101 | 121 | 140 | 165 | 184 | 203 | 229 | 305 | | | | | |
| | CLASS 125 | | 89 | 98 | 108 | 127 | 152 | 178 | 190 | 229 | 297 | 152 | 178 | 190 | 229 | |
| FLANGE THINCKNESS | | C | 13 | 13 | 13 | 16 | 19 | 19 | 19 | 24 | 25 | 19 | 19 | 19 | 24 | 25 |
| SIZE OF PLUG SQUIRE | | D | 19 | 22 | 22 | 27 | 31 | 38 | 41 | 47 | 49 | 27 | 31 | 38 | 41 | 49 |
| DEPTH PF PLUG SQUARE | | E | 20 | 20 | 20 | 25 | 28 | 30 | 49 | 50 | 60 | 25 | 28 | 30 | 49 | 60 |
| CENTER LINE TO TOP OF PLUG | | F | 100 | 114 | 120 | 157 | 173 | 196 | 226 | 247 | 325 | 156 | 172 | 197 | 222 | 305 |
| CENTER LINE TO BOTTOM FO BODY | | G | 34 | 46 | 49 | 65 | 76 | 92 | 107 | 136 | 185 | 70 | 90 | 101 | 114 | 175 |
| WEIGHT (kgs.) | | | 2.95 | 4.1 | 5.5 | 10 | 15.5 | 22 | 30 | 51 | 100 | 13 | 18 | 25 | 35 | 83 |
| WRENCH NOS. | | | 1W | 2W | 3W | 4W | 5W | 6W | 7W | 8W | 10W | 4W | 5W | 6W | 7W | 10W |

Note : Due to constant up gradation, dimensions are subject to change by the manufacturer.